

PRODUCT SPECIFICATION

SPEAKERS

Model	Description	Diameter	Mounting Depth	RMS Power	Impedance	Grill Options	Colour Options
MX770-CCX	Cockpit Coaxial Speaker	195mm	80mm	25W - 150W	4ohms	Classic or Sports	White or Titanium/Black
MX650-CCX	Cockpit Coaxial Speaker	165mm	70mm	15W - 100W	4ohms	Classic or Sports	White or Titanium/Black
M880-CCX	Cockpit Coaxial Speaker	224mm	132mm	50W - 250W	4ohms	Classic or Sports	White or Titanium/Black
M770-CCX	Cockpit Coaxial Speaker	195mm	80mm	40W - 170W	4ohms	Classic or Sports	White or Titanium/Black
M650-CCX	Cockpit Coaxial Speaker	165mm	75mm	25W - 150W	4ohms	Classic or Sports	White or Titanium/Black

SUBWOOFERS

Model	Description	Diameter	Mounting	RMS Power	Impedance	Grill Options	Colour Options
M10IB5	Subwoofer Driver - Infinite	250mm	151mm	75W - 250W	4ohms	Classic or Sports	White or Titanium/Black
MX10IB3	Subwoofer Driver - Infinite	250mm	128mm	55W - 175W	4ohms	Classic or Sports	White or Titanium/Black

M12v AMPLIFIERS

M400/4	400W Class D Amplifier	4	52 x 180mm	75W x 4 @ 4Ω / 100W x 4 @ 2Ω / Bridged: 150W x 2 @ 8Ω / Bridged: 200W x 2 @ 4Ω			
M600/1	600W Class D Amplifier	1	52 x 217 x 180mm	400W x 1 @ 4Ω / 600W x 1 @ 2Ω			
M600/6	600W Class D Amplifier	6	52 x 260 x 180mm	75W x 6 @ 4Ω / 100w x 6 @ 2Ω / Bridged: 150W x 3 @ 8Ω / Bridged: 200W x 3 @ 4Ω			
M700/5	700W Class D Amplifier	5	52 x 260 x 180mm	75W x 4 + 180W x 1 @ 4Ω / 100W x 4 + 300W x 1 @ 2Ω / Bridged: 200W x 2 @ 4Ω			
M800/8v2	800W Class D Amplifier	8	52 x 374 x 180mm	75W x 8 @ 4Ω / 100w x 8 @ 2Ω / Bridged: 200W x 4 @ 4Ω			

ACCESSORIES

MHD-RLC	Remote Level Control	5.5m cable
---------	----------------------	------------

MX AMPLIFIERS

MX280/4	280W MX Class D Amp	4	45 x 220 x 78mm	50W x 4 @ 4Ω / 70W x 4 @ 2Ω / Bridged: 100W x 2 @ 8 ohms / Bridged / 140W x 2 @			
MX300/1	300W MX Class D Amp	1	45 x 220 x 78.5mm	160W x 1 @ 4Ω / 220w x 1 @ 3Ω / 300W x 1 @ 2Ω			
MX500/1	500W MX Class D Amp	1	237 x 114.5 x 45	300W x 1 @ 4Ω / 400w x 1 @ 3Ω / 500W x 1 @ 2Ω			
MX 500/4	500W MX Class D Amp	4	237 x 114.5 x 45	70W x 4 @ 4Ω / 125w x 4 @ 2Ω / Bridged: 180W x 2 @ 8Ω / Bridged 250W x 2 @ 4Ω			

ACCESSORIES

M-RBC-1	Remote Bass Control	5m cable
---------	---------------------	----------

CONNECTIVITY

Model	Description	Voltage	Output
MBT-CRX	Bluetooth Audio Controller & Receiver	8v-28v DC	Stereo RCA
MBT-RX	Bluetooth Audio Receiver	8v-28v DC	Stereo RCA

MEDIA MASTER

Model	Description	Dimension	Mounting	IP Rating	Voltage	Channel	Current
MM100s	Media Master 100	99x151mm	45.2mm	IP67	10v-16v DC	4x RCA	1.5A
MMR-20	Media Master Remote	60mm	29mm	IP66			
MMC-6	Remote extension 6 foot						
MMC-25	Remote extension 25 foot						
MMC-2Y	Remote Y-Cable						
MMC-DN2K-1	N2k adapter cable 1ft.						
MMC-DN2K-6	N2k adapter cable 6ft.						

POWER CONNECTIONS AND FUSES

XMD-MCB-30	Waterproof, Ignition-protected Circuit Breaker: 30 AMP
XMD-MCB-40	Waterproof, Ignition-protected Circuit Breaker: 40 AMP
XMD-MCB-50	Waterproof, Ignition-protected Circuit Breaker: 50 AMP
XMD-MCB-60	Waterproof, Ignition-protected Circuit Breaker: 60 AMP
XMD-MCB-80	Waterproof, Ignition-protected Circuit Breaker: 80 AMP
XMD-PCS50A-1-L10	Power connection System (within 10 ft of Battery)
XMD-PCS50A-1-L20	Power connection System (within 20 ft of Battery)
XD-MAXI-30	Maxi Fuse - 30A
XD-MAXI-40	Maxi Fuse - 40A
XD-MAXI-50	Maxi Fuse - 50A
XD-MAXI-60	Maxi Fuse - 60A
XD-MAXI-80	Maxi Fuse - 80A
XD-MFBW-MAXI	Maxi Fuse Block

AUDIO CONNECTIONS

XMD-3.5MM-PNL	3.5mm dash mount
XMD-USB/3.5MM-PNL	3.5mm + USB dash mount
XMD-WHTAIC2-1.5	RCA 2 Channel, 1.5ft
XMD-WHTAIC2-3	RCA 2 Channel, 3ft
XMD-WHTAIC2-6	RCA 2 Channel, 6ft
XMD-WHTAIC2-12	RCA 2 Channel, 12ft
XMD-WHTAIC2-25	RCA 2 Channel, 25ft
XMD-WHTAIC4-6	RCA 4 channel 6ft
XMD-WHTAIC4-12	RCA 4 channel 12ft
XMD-WHTAIC4-25	RCA 4 channel 25ft
XMD-WHTAICY-1F2M	RCA Y-Adaptor 1F 2M
XMD-WHTAICY-1M2F	RCA Y-Adaptor 1M 2F
XM-WHTSC16-25	Speaker Cable - 25ft. Pack
XM-WHTSC16-500	Speaker Cable - 500ft. Bulk
XC-MINIAIC2-3	3.5mm cable 3ft
XC-MINIAIC2-6	3.5mm cable 6ft
XD-MINIRCA2-6	RCA to 3.5mm cable 6ft